



Super stable
and stackable

Easy Box Clip

An innovative plastic clip with twist closure gives this reusable box extra stability. The system clips together in a flash to create a completely gap-free box, which can later be disassembled for compact storage.

These stackable OSB boxes have permanent plastic connectors for rapid, secure assembly – no need for any tools. The Easy Box Clip is produced on a customer-/product-specific basis to match individual requirements based on the contents. This saves on unnecessary empty space during storage and transport. For extra security, the ergonomically constructed clip-together system also has a surrounding strap. The contents can be accessed immediately the lid is removed. A seal fastened to the joins indicates when the box has been opened.

Easy Box Clip

		Easy Box Clip	Easy Box Clip+
Fastening system		Slot-together with plastic clip	Slot-together with plastic clip
Contents	Max. length	2320	2320
	Max. width	1070	1070
	Max. height	1120	1120
	Max. weight in kg	≤ 500	> 500
Maximum external container dimensions	Max. length	2500	2500
	Max. width	1250	1250
	Max. height	1250	1250
Material and material thickness – sides& lid	Material, sides	OSB	OSB
	Material thickness, sides	12	12
	Wooden brace, sides	-	Optional
	Additional security with screws	-	-
	Material, lid	OSB	OSB
	Material thickness, lid	12	12
	Wooden brace, lid	-	-
	Lid fastening	Plastic or steel strap	Gaffer tape
	Additional security with screws	-	-
Edge protection	-	Optional	
Base	Design	Transverse skids	Transverse/longitudinal skids Pallet base
	Pallet base	-	Available from length 850 mm and width 800 mm
	Material	Plywood	Plywood
	Thickness (mm)	12	15
	Longitudinal sections (mm)	60 × 100	100 × 100
	Längsbalken (mm)	-	100 × 60
	Top (mm)	-	100 × 100
Steel cables	-	Optional	
Markings and certifications	Fragile (glass symbol)	Standard	Standard
	Top (arrow symbol)	Standard	Standard
	Keep dry (umbrella symbol)	Standard	Standard
	ISPM 15	Standard	Standard
	Easy Open Line™ (Logo)	Standard	Standard
	Centre of gravity	Optional	Optional
	Do not roll	Optional	Optional
	Do not use forklift	Optional	Optional
	Attach here	Optional	Optional
	Weight limit for stacked load	-	Optional
Stacking limit	-	Optional	
ISTA 3E load and stability test	Coming soon	Coming soon	
Recommended minimum storage requirements	Outdoors	Possible, covered with Valeron film	Possible, covered with Valeron film
	Outdoors, covered	✓	✓
	Indoor warehouse	✓	✓
	Warehouse with climate control	✓	✓
Delivery time from order		48 hours	48 hours

Note: dimensions in mm; weight and load specifications in kg

HEADQUARTERS

cargopack tägi ag
Schiffmühlestrasse 8
CH-5417 Untersiggenthal

Telephone +41 (0) 56 298 55 00
Fax +41 (0) 56 298 55 10

info@cargopacktaegi.ch
www.cargopacktaegi.ch

SWITZERLAND BRANCHES

4133 Pratteln
5036 Oberentfelden
5332 Rekingen
8050 Zürich-Oerlikon
9405 Rohrschacherberg



**EASY
OPEN
LINE**