



# Easy Box Light

With no nails or screws, the Easy Box Light can be opened without a single tool. The practical slot-together box comes in standard sizes and can be used again and again.

The Easy Box Light is delivered in a compact form and can be stored in minimal space. Packing and unpacking the assembled box is virtually effortless. The stackable OSB boxes can be constructed very quickly by one person, while the slotted assembly facilitates particularly ergonomic and fast packing. To unpack the box, just remove the strap, take off the lid, and the contents are immediately accessible. A seal fastened to the joints indicates when the box has been opened.

# Easy Box Light

		Easy Box Light	Easy Box Light+
<b>Fastening system</b>		Slot-together with wooden hooks	Slot-together with wooden hooks
<b>Contents</b>	Max. length	2320	2320
	Max. width	1070	1070
	Max. height	1120	1120
	Max. weight in kg	≤ 500	> 500
<b>Maximum external container dimensions</b>	Max. length	2500	2500
	Max. width	1250	1250
	Max. height	1250	1250
<b>Material and material thickness – sides&amp; lid</b>	Material, sides	OSB	OSB
	Material thickness, sides	12	12
	Wooden brace, sides	-	Optional
	Additional security with screws	-	-
	Material, lid	OSB	OSB
	Material thickness, lid	12	12
	Wooden brace, lid	-	-
	Lid fastening	Plastic or steel strap	Gaffer tape
	Additional security with screws	-	-
<b>Base</b>	Design	Transverse skids	Transverse/longitudinal skids Pallet base
	Pallet base	-	available from length 850 mm/ width 800 mm
	Material	Plywood	Plywood
	Thickness (mm)	12	15
	Longitudinal sections (mm)	60 x 100	100 x 100
	Längsbalken (mm)	-	100 x 60
	Top (mm)	-	100 x 100
	Steel cables	-	Available
<b>Markings and certifications</b>	<b>Fragile (glass symbol)</b>	Standard	Standard
	<b>Top (arrow symbol)</b>	Standard	Standard
	<b>Keep dry (umbrella symbol)</b>	Standard	Standard
	<b>ISPM 15</b>	Standard	Standard
	<b>Easy Open Line™ (Logo)</b>	Standard	Standard
	Centre of gravity	Optional	Optional
	Do not roll	Optional	Optional
	Do not use forklift	Optional	Optional
	Attach here	Optional	Optional
	Weight limit for stacked load	-	Optional
	Stacking limit	-	Optional
ISTA 3E load and stability test	Available	Available	
<b>Recommended minimum storage requirements</b>	Outdoors	possible, covered with Valeron film	possible, covered with Valeron film
	Outdoors, covered	✓	✓
	Indoor warehouse	✓	✓
	Warehouse with climate control	✓	✓
<b>Delivery time from order</b>		48 hours	48 hours

Note: dimensions in mm; weight and load specifications in kg

## HEADQUARTERS

cargopack tägi ag  
Schiffmühlestrasse 8  
CH-5417 Untersiggenthal

Telephone +41 (0) 56 298 55 00  
Fax +41 (0) 56 298 55 10

info@cargopacktaegi.ch  
www.cargopacktaegi.ch

## SWITZERLAND BRANCHES

4133 Pratteln  
5036 Oberentfelden  
5332 Rekingen  
8050 Zürich-Oerlikon  
9405 Rohrschacherberg



**EASY  
OPEN  
LINE**