



Variant
"Front"



TEAR OPEN
AND DIVE IN



Variant
"Cover"



No experience
necessary!

Easy Box Once

The perfect solution for fragile goods: with state of the art tear-open technology, you can rest assured that opening the Easy Box Once will leave even the most fragile products unscathed.

Opening this box is as simple as one-two-three. The Easy Box Once is constructed from OSB sections and can be opened quickly and safely: the sides are opened with the aid of an opening cord, and then the whole thing is lifted off like a hood ("Cover" variant). Alternatively, for a box that is easy to open and close back up, look no further than the "Front" variant. In this model, just one side tears open and the front boards are pulled out. Either variant can be opened quickly and easily with no tools, so no risk of damaging the contents. The box sizes are matched to the contents, avoiding unnecessary empty spaces.

Easy Box Once

		Easy Box Once «Front»	Easy Box Once «Cover»
Fastening system		Screwed/nailed	Screwed/nailed
Contents	Max. length	2320	2320
	Max. width	1070	1070
	Max. height	1120	1120
	Max. weight in kg	On request	On request
Maximum external container dimensions	Max. length	2500	2500
	Max. width	1250	1250
	Max. height	1250	1250
Material and material thickness – sides& lid	Material, sides	OSB	OSB
	Material thickness, sides	12	12
	Wooden brace, sides	-	Optional
	Additional security with screws	-	-
	Material, lid	OSB	OSB
	Material thickness, lid	12	12
	Wooden brace, lid	-	-
	Lid fastening	Screwed/nailed	Screwed/nailed
	Additional security with screws	-	-
	Edge protection	-	-
Base	Design	Transverse skids	Transverse/longitudinal skids Pallet base
	Pallet base	-	Available from length 850 mm and width 800 mm
	Material	Plywood	Solid wood
	Thickness (mm)	up to 25	up to 50
	Longitudinal sections (mm)	100 × 100	100 × 100
	Längsbalken (mm)	-	100 × 100
	Top (mm)	-	100 × 100
	Steel cables	-	Optional
Markings and certifications	Fragile (glass symbol)	Standard	Standard
	Top (arrow symbol)	Standard	Standard
	Keep dry (umbrella symbol)	Standard	Standard
	ISPM 15	Standard	Standard
	Easy Open Line™ (Logo)	Standard	Standard
	Centre of gravity	Available	Available
	Do not roll	Available	Available
	Do not use forklift	Available	Available
	Attach here	Optional	Optional
	Weight limit for stacked load	Optional	Optional
	Stacking limit	Optional	Optional
ISTA 3E load and stability test	-	-	
Recommended minimum storage requirements	Outdoors	possible, covered with Valeron film	possible, covered with Valeron film
	Outdoors, covered	✓	✓
	Indoor warehouse	✓	✓
	Warehouse with climate control	✓	✓
Delivery time from order		48 hours	48 hours

Note: dimensions in mm; weight and load specifications in kg

HEADQUARTERS

cargopack tägi ag
Schiffmühlestrasse 8
CH-5417 Untersiggenthal

Telephone +41 (0) 56 298 55 00
Fax +41 (0) 56 298 55 10

info@cargopacktaegi.ch
www.cargopacktaegi.ch

SWITZERLAND BRANCHES

4133 Pratteln
5036 Oberentfelden
5332 Rekingen
8050 Zürich-Oerlikon
9405 Rohrschacherberg



**EASY
OPEN
LINE**