



Easy Box Slide

This transport box features customisable horizontal divisions – match the shelves to your product dimensions. The flexible use of space and stable plywood shelves make this the ideal box for multiple uses.

The shelves and compartments can be adjusted individually to match your particular requirements. They are easily accessed from one side, meaning that the contents can be slid into tight spaces and removed again later without disassembling the box. The Easy Box Slide has stable OSB sides and strong plywood shelves that can be positioned separately each time you use the box. It can be closed with either a safety screw or a locking latch.

Easy Box Slide

		Easy Box Slide	Easy Box Slide+
Fastening system		Slide opening	Slide opening
Contents	Max. length	2320	2320
	Max. width	1070	1070
	Max. height	1120	1120
	Max. weight in kg	≤ 500	> 500
Maximum external container dimensions	Max. length	2500	2500
	Max. width	1250	1250
	Max. height	1250	1250
Material and material thickness – sides& lid	Material, sides	OSB	OSB
	Material thickness, sides	25	25
	Wooden brace, sides	-	Optional
	Additional security with screws	Front screwed	Front screwed
	Material, lid	OSB	OSB
	Material thickness, lid	25	25
	Wooden brace, lid	-	-
	Lid fastening	-	-
	Additional security with screws	-	-
Edge protection	-	Optional	
Base	Design	Transverse skids	Transverse/longitudinal skids Pallet base
	Pallet base	-	Available from length 850 mm and width 800 mm
	Material	OSB	OSB
	Thickness (mm)	25	25
	Longitudinal sections (mm)	100 × 100	Block 95 × 95 × 78
	Längsbalken (mm)	-	100 × 100
	Top (mm)	-	-
	Steel cables	-	Optional
Markings and certifications	Fragile (glass symbol)	Standard	Standard
	Top (arrow symbol)	Standard	Standard
	Keep dry (umbrella symbol)	Standard	Standard
	ISPM 15	Standard	Standard
	Easy Open Line™ (Logo)	Standard	Standard
	Centre of gravity	Optional	Optional
	Do not roll	Optional	Optional
	Do not use forklift	Optional	Optional
	Attach here	Optional	Optional
	Weight limit for stacked load	-	Optional
	Stacking limit	-	Optional
ISTA 3E load and stability test	Available	Available	
Recommended minimum storage requirements	Outdoors	Possible, covered with Valeron film	Possible, covered with Valeron film
	Outdoors, covered	✓	✓
	Indoor warehouse	✓	✓
	Warehouse with climate control	✓	✓
Delivery time from order		48 hours	48 hours

Note: dimensions in mm; weight and load specifications in kg

HEADQUARTERS

cargopack tägi ag
Schiffmühlestrasse 8
CH-5417 Untersiggenthal

Telephone +41 (0) 56 298 55 00
Fax +41 (0) 56 298 55 10

info@cargopacktaegi.ch
www.cargopacktaegi.ch

SWITZERLAND BRANCHES

4133 Pratteln
5036 Oberentfelden
5332 Rekingen
8050 Zürich-Oerlikon
9405 Rohrschacherberg



**EASY
OPEN
LINE**